

Energy Saver A/S - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
11987	175/65R15 84H	65,000 Mile	BSW	480/A/B	5" - 6"	7" on 5"	24.0"	867	9.5	1102@44	14.81 lbs
34184	195/65R15 91T	65,000 Mile	BSW	480/A/B	5.5" - 7"	7.9" on 6"	25.0"	832	8.0	1356@44	18.1 lbs
66109	205/55R16 91H	65,000 Mile	BSW	480/A/B	5.5" - 7.5"	8.4" on 6.5"	24.9"	836	8.5	1356@44	19.95 lbs
15325	P205/60R16 91V	55,000 Mile	BSW	480/A/A	5.5" - 7.5"	8.2" on 6"	25.7"	810	8.5	1356@44	21.16 lbs
34895	205/60R16 92H	65,000 Mile	BSW	480/A/A	5.5" - 7.5"	8.2" on 6"	25.7"	810	9.0	1389@44	20.88 lbs
42830	P205/65R16 94S	65,000 Mile	BSW	480/A/B	5.5" - 7.5"	8.2" on 6"	26.5"	786	9.5	1477@44	22.62 lbs
03507	205/65R16 95H	65,000 Mile	BSW	480/A/B	5.5" - 7.5"	8.2" on 6"	26.5"	786	9.0	1521@44	21.91 lbs
72288	P215/50R17 90V	55,000 Mile	BSW	480/A/A	6" - 7.5"	8.9" on 7"	25.5"	815	9.0	1323@44	21.12 lbs
16798	215/50R17 91H	65,000 Mile	BSW	480/A/A	6" - 7.5"	8.9" on 7"	25.5"	815	9.0	1356@44	20.46 lbs
33539	215/50R17 91H	65,000 Mile	BSW	480/A/B	6" - 7.5"	8.9" on 7"	25.5"	815	8.0	1356@44	23.13 lbs
77092	215/55R16 93V	55,000 Mile	BSW	480/A/B	6" - 7.5"	8.9" on 7"	25.3"	823	8.0	1433@44	20.35 lbs
51569	215/55R17 94V	55,000 Mile	BSW	480/A/B	6" - 7.5"	8.9" on 7"	26.3"	791	9.5	1477@44	23.02 lbs
11387	P215/65R17 98T	65,000 Mile	BSW	480/A/B	6" - 7.5"	8.7" on 6.5"	28.0"	742	9.5	1653@44	25.66 lbs
03458	P225/50R17 93V	55,000 Mile	BSW	480/A/A	6" - 8"	9.2" on 7"	25.9"	803	9.5	1433@44	22.18 lbs
18116	225/50R17 94V	55,000 Mile	BSW	480/A/A	6" - 8"	9.2" on 7"	25.9"	803	8.5	1477@44	22.71 lbs
47360	P225/65R17 100T	65,000 Mile	BSW	480/A/B	6" - 8"	9" on 6.5"	28.5"	730	10.0	1764@44	26.46 lbs
83418	235/45R18 94V	55,000 Mile	BSW	480/A/B	7.5" - 9"	9.3" on 8"	26.3"	790	8.5	1477@44	24.49 lbs
60662	P235/50R17 95T	65,000 Mile	BSW	480/A/B	6.5" - 8.5"	9.7" on 7.5"	26.3"	791	9.5	1521@44	23.85 lbs
23609	235/50R17 96H	65,000 Mile	BSW	480/A/A	6.5" - 8.5"	9.7" on 7.5"	26.3"	791	9.0	1565@44	24.38 lbs
14031	P235/50R18 97V	55,000 Mile	BSW	480/A/A	6.5" - 8.5"	9.7" on 7.5"	27.3"	762	9.5	1609@44	25.9 lbs
24910	235/55R17 99H	65,000 Mile	BSW	480/A/B	6.5" - 8.5"	9.6" on 7.5"	27.2"	766	8.5	1709@44	26.21 lbs
78923	LT235/80R17/E 120/117R	50,000 Mile	BSW	//	6" - 7.5"	9.2" on 6.5"	31.8"	654	11.5	3085@80	43.61 lbs
85637	P265/65R18 112T	65,000 Mile	BSW	480/A/B	7.5" - 9.5"	10.7" on 8"	31.5"	659	9.0	2469@44	35.32 lbs