

Latitude Tour HP - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
25842	215/65R16 98H	55,000 Mile	BSW	440/A/A	6" - 7.5"	8.7" on 6.5"	27.0"	770	10.5	1503@44	25.64 lbs
75351	225/65R17 102H	55,000 Mile	BSW	440/A/A	6" - 8"	9" on 6.5"	28.5"	730	9.5	1704@51	27.07 lbs
26136	235/50R18 97V	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.7" on 7.5"	27.3"	762	10.0	1463@44	28.22 lbs
52571	235/55R19 101H	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.7" on 7.5"	29.5"	704	9.5	1654@51	31.97 lbs
05146	235/55R19 101V	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.7" on 7.5"	29.2"	713	10.0	1654@51	32.12 lbs
15474	235/55R19 101V	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.6" on 7.5"	29.2"	713	9.5	1654@51	30.42 lbs
18386	P235/55R20 102H	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.7" on 7.5"	30.2"	690	10.0	1704@44	33.84 lbs
20377	P235/60R18 102V	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.5" on 7"	29.1"	715	10.0	1704@51	29.26 lbs
29269	235/60R18 103H	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.5" on 7"	29.1"	715	10.0	1754@51	32.08 lbs
31480	235/60R18 103V	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.5" on 7"	29.1"	715	10.0	1754@51	32.3 lbs
33988	235/60R18 103V	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.5" on 7"	29.1"	715	9.5	1754@51	28.66 lbs
03870	235/60R18/XL 107V	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.5" on 7"	29.1"	715	9.5	1954@50	31.08 lbs
33809	235/65R17 104H	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.5" on 7"	29.1"	716	9.5	1804@51	30.53 lbs
19025	235/65R17 104V	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.5" on 7"	29.1"	716	9.5	1804@51	30.53 lbs
01431	P235/65R18 104H	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.5" on 7"	30.0"	692	10.0	1804@44	33.4 lbs
24459	235/65R18/XL 110V	55,000 Mile	BSW	440/A/A	6.5" - 8.5"	9.4" on 7"	30.0"	692	9.5	2124@50	30.31 lbs
10407	245/45R19 98V	55,000 Mile	BSW	440/A/A	7.5" - 9"	9.5" on 8"	27.7"	751	9.5	1502@44	31.53 lbs
34924	245/45R20/XL 103W	45,000 Mile	BSW	440/A/A	7.5" - 9"	9.5" on 8"	28.6"	726	9.5	1754@50	29.65 lbs
41671	245/55R19 103H	55,000 Mile	BSW	440/A/A	7" - 8.5"	9.9" on 7.5"	29.6"	702	10.0	1754@44	31.79 lbs
44077	P245/60R18 104H	55,000 Mile	BSW	440/A/A	7" - 8.5"	9.8" on 7"	29.6"	703	10.0	1804@44	34.06 lbs
98018	245/60R18 105H	55,000 Mile	BSW	440/A/A	7" - 8.5"	9.8" on 7"	29.6"	705	10.0	1854@44	32.69 lbs
43880	245/60R18 105V	55,000 Mile	BSW	440/A/A	7" - 8.5"	9.7" on 7"	29.5"	703	9.0	1854@44	32.25 lbs
37853	255/50R19 103V	55,000 Mile	BSW	440/A/A	7" - 9"	10.4" on 8"	29.1"	715	9.5	1754@51	32.19 lbs
38366	255/50R19/XL 107H	55,000 Mile	BSW	440/A/A	7" - 9"	10.6" on 8"	29.1"	715	10.0	1954@50	34.22 lbs

Latitude Tour HP - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
09483	255/50R19/XL 107H	30,000 Mile	BSW	400/A/A	7" - 9"	10.4" on 8"	29.1"	715	10.0	1954@50	40.54 lbs
94455	255/50R20/XL 109W	45,000 Mile	BSW	440/A/A	7" - 9"	10.4" on 8"	30.0"	691	9.5	2064@50	34.13 lbs
98728	255/55R18 105H	55,000 Mile	BSW	440/A/A	7" - 9"	10.4" on 8"	29.0"	717	9.5	1854@51	31.53 lbs
61618	255/55R18 105V	55,000 Mile	BSW	440/A/A	7" - 9"	10.4" on 8"	29.0"	717	9.5	1854@51	30.86 lbs
09597	255/55R18/XL 109H	30,000 Mile	BSW	400/A/A	7" - 9"	10.4" on 8"	29.0"	717	10.0	2064@50	42.35 lbs
89039	255/55R18/XL 109V	55,000 Mile	BSW	440/A/A	7" - 9"	10.4" on 8"	29.0"	717	9.5	2064@50	34.72 lbs
06518	255/55R19/XL 111W	45,000 Mile	BSW	440/A/A	7" - 9"	10.4" on 8"	30.0"	692	10.0	2185@50	33.95 lbs
91214	265/45R20 104V	55,000 Mile	BSW	440/A/A	8.5" - 10"	10.4" on 9"	29.3"	708	9.5	1804@51	30.42 lbs
59682	265/45R21 104W	45,000 Mile	BSW	440/A/A	8.5" - 10"	10.4" on 9"	30.3"	685	9.5	1804@51	34.39 lbs
73564	265/50R19/XL 110V	55,000 Mile	BSW	440/A/A	7.5" - 9.5"	10.9" on 8.5"	29.5"	705	10.0	2124@50	33.6 lbs
15845	P265/60R18 109H	55,000 Mile	BSW	440/A/A	7.5" - 9.5"	10.7" on 8"	30.5"	682	10.0	2064@51	35.49 lbs
44567	265/60R18 110V	55,000 Mile	BSW	440/A/A	7.5" - 9.5"	10.7" on 8"	30.5"	682	9.5	2124@51	37.19 lbs
07767	275/40ZR20/XL 106W	45,000 Mile	BSW	440/A/A	9" - 11"	10.9" on 9.5"	28.7"	726	10.0	1904@50	32.69 lbs
04493	275/45R19/XL 108V	55,000 Mile	BSW	440/A/A	8.5" - 10.5"	10.8" on 9"	28.8"	723	9.5	2004@50	30.47 lbs
07769	P275/60R20 114H	55,000 Mile	BSW	440/A/A	7.5" - 9.5"	11" on 8"	33.0"	630	10.0	2365@44	39.15 lbs
32901	285/50R20 112V	55,000 Mile	BSW	440/A/A	8" - 10"	11.5" on 9"	31.0"	665	10.0	2245@51	39.37 lbs
24388	285/60R18/XL 120V	55,000 Mile	BSW	440/A/A	8" - 10"	11.5" on 8.5"	31.4"	661	10.0	2806@50	39.9 lbs
38951	295/40R20 106V	55,000 Mile	BSW	440/A/A	10" - 11.5"	11.8" on 10.5"	29.3"	710	9.5	1904@51	33.4 lbs