

Pilot Sport A/S 3 - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
96862	205/40R17/XL 84V	45,000 Mile	BSW	500/AA/A	7" - 8"	8.3" on 7.5"	23.5"	887	10.0	1102@50	20.13 lbs
23431	255/55R19/XL 111V	45,000 Mile	BSW	500/AA/A	7" - 9"	10.4" on 8"	30.1"	692	9.5	2403@50	33.29 lbs
91057	275/40R20/XL 106V	45,000 Mile	BSW	500/AA/A	9" - 11"	10.9" on 9.5"	28.7"	726	10.0	2094@44	32.85 lbs
79683	275/45R20/XL 110V	45,000 Mile	BSW	500/AA/A	8.5" - 10.5"	10.7" on 9"	29.8"	699	9.5	2337@50	32.85 lbs
74866	275/50R19/XL 112V	45,000 Mile	BSW	500/AA/A	7.5" - 9.5"	11.2" on 8.5"	29.9"	696	9.5	2469@50	33.62 lbs
73430	305/40R20/XL 112V	45,000 Mile	BSW	500/AA/A	10" - 12"	12.3" on 11"	29.6"	702	9.5	2469@50	34.61 lbs
34397	315/35R20/XL 110V	45,000 Mile	BSW	500/AA/A	10.5" - 12.5"	12.6" on 11"	28.7"	726	10.0	2337@44	34.83 lbs