

Pilot Super Sport - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
30661	205/45ZR17/XL (88Y)	30,000 Mile	BSW	300/AA/A	6.5" - 7.5"	8.1" on 7"	24.3"	858	10.0	1235@50	19.71 lbs
68599	205/45ZR17/XL (88Y)	30,000 Mile	BSW	300/AA/A	6.5" - 7.5"	8.1" on 7"	24.3"	858	10.0	1235@50	19.64 lbs
15493	225/35ZR18/XL (87Y)	30,000 Mile	BSW	300/AA/A	7.5" - 9"	9.1" on 8"	24.2"	859	10.0	1201@50	20.0 lbs
84453	225/35ZR19/XL (88Y)	30,000 Mile	BSW	300/AA/A	7.5" - 9"	9.1" on 8"	25.2"	824	9.5	1235@50	20.94 lbs
49739	225/40ZR18 88Y	30,000 Mile	BSW	300/AA/A	7.5" - 9"	9.1" on 8"	25.1"	829	9.0	1235@51	20.37 lbs
91154	225/40ZR18/XL 92Y	30,000 Mile	BSW	300/AA/A	7.5" - 9"	9.1" on 8"	25.1"	829	9.0	1389@50	20.37 lbs
82315	225/40ZR18/XL 92Y	30,000 Mile	BSW	300/AA/A	7.5" - 9"	9.1" on 8"	25.1"	829	10.0	1389@50	20.37 lbs
18580	225/45ZR18/XL (95Y)	30,000 Mile	BSW	300/AA/A	7" - 8.5"	8.9" on 7.5"	25.9"	802	9.0	1521@50	22.16 lbs
18607	235/35ZR19/XL (91Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.5" on 8.5"	25.5"	817	10.0	1356@50	22.51 lbs
07688	235/35ZR20/XL (92Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.5" on 8.5"	26.5"	786	10.0	1389@50	22.38 lbs
01088	245/35ZR18/XL 92Y	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.7" on 8.5"	24.5"	840	9.0	1389@50	22.29 lbs
25687	P245/35ZR19 (89Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	25.8"	807	8.5	1279@51	27.43 lbs
30260	245/35ZR19/XL 93Y	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	25.8"	807	10.0	1433@50	23.15 lbs
08781	245/35ZR19/XL (93Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	25.8"	807	10.0	1433@50	23.48 lbs
05325	245/35ZR20/XL (95Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	26.8"	777	9.0	1521@50	24.25 lbs
20206	245/35ZR20/XL (95Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	26.8"	777	9.0	1521@50	23.21 lbs
74634	245/35ZR20/XL (95Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	26.8"	777	10.0	1521@50	23.32 lbs
90983	245/35ZR20/XL (95Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	26.8"	777	9.0	1521@50	23.41 lbs
10412	245/35ZR20/XL (95Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	26.8"	777	9.0	1521@50	23.41 lbs
18333	245/35ZR20/XL 95Y	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	26.8"	777	9.0	1521@50	23.19 lbs
22114	245/35ZR21/XL (96Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	27.8"	749	9.5	1565@50	24.96 lbs
66697	245/35ZR21/XL (96Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	27.8"	749	10.0	1565@50	24.98 lbs
31708	245/35ZR21/XL (96Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	27.8"	749	10.0	1565@50	24.98 lbs
69693	P245/40ZR18 (93Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	25.7"	809	9.0	1433@51	27.73 lbs

Pilot Super Sport - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
08385	245/40ZR18/XL 97Y	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	25.7"	809	10.0	1609@50	23.79 lbs
36814	245/40ZR19/XL (98Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	26.7"	778	10.0	1653@50	25.02 lbs
04032	245/40ZR20/XL (99Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	27.7"	750	9.0	1709@50	26.46 lbs
53473	245/40RF21 96Y	30,000 Mile	BSW	300/AA/A	8" - 9.5"	9.8" on 8.5"	28.7"	725	9.5	1565@51	30.64 lbs
47308	255/30ZR19/XL (91Y)	30,000 Mile	BSW	300/AA/A	8.5" - 9.5"	10.2" on 9"	25.1"	829	9.5	1356@50	24.56 lbs
03772	255/35ZR18/XL (94Y)	30,000 Mile	BSW	300/AA/A	8.5" - 10"	10.2" on 9"	25.0"	832	8.5	1477@50	24.38 lbs
90967	255/35ZR19 (92Y)	30,000 Mile	BSW	300/AA/A	8.5" - 10"	10.2" on 9"	26.0"	799	10.0	1389@51	24.43 lbs
21931	255/35ZR19/XL (96Y)	30,000 Mile	BSW	300/AA/A	8.5" - 10"	10.2" on 9"	26.0"	799	10.0	1565@50	23.52 lbs
31567	255/35ZR19/XL (96Y)	30,000 Mile	BSW	300/AA/A	8.5" - 10"	10.2" on 9"	26.0"	799	10.0	1565@50	24.36 lbs
08292	255/35ZR19/XL (96Y)	30,000 Mile	BSW	300/AA/A	8.5" - 10"	10.2" on 9"	26.0"	799	10.0	1565@50	24.52 lbs
48527	255/35ZR20/XL (97Y)	30,000 Mile	BSW	300/AA/A	8.5" - 10"	10.2" on 9"	27.0"	770	7.0	1609@50	24.29 lbs
51251	255/35ZR21/XL (98Y)	30,000 Mile	BSW	300/AA/A	8.5" - 10"	10.2" on 9"	28.0"	743	10.0	1653@50	26.46 lbs
40116	255/40ZR18 (95Y)	30,000 Mile	BSW	300/AA/A	8.5" - 10"	10.2" on 9"	26.0"	799	10.0	1521@51	23.61 lbs
01806	255/40ZR18/XL (99Y)	30,000 Mile	BSW	300/AA/A	8.5" - 10"	10.2" on 9"	26.0"	799	10.0	1709@50	25.33 lbs
13251	255/40ZR18/XL (99Y)	30,000 Mile	BSW	300/AA/A	8.5" - 10"	10.2" on 9"	26.0"	799	9.5	1709@50	23.68 lbs
94380	255/40ZR20/XL (101Y)	30,000 Mile	BSW	300/AA/A	8.5" - 10"	10.2" on 9"	28.0"	742	9.0	1819@50	27.31 lbs
00264	255/45ZR19 (100Y)	30,000 Mile	BSW	300/AA/A	8" - 9.5"	10" on 8.5"	28.1"	741	9.0	1764@51	27.62 lbs
04997	265/30ZR20/XL (94Y)	30,000 Mile	BSW	300/AA/A	9" - 10"	10.7" on 9.5"	26.3"	791	9.0	1477@50	24.01 lbs
76955	265/30ZR22/XL (97Y)	30,000 Mile	BSW	300/AA/A	9" - 10"	10.7" on 9.5"	28.3"	735	10.0	1609@50	29.56 lbs
43081	265/35ZR19/XL 98Y	30,000 Mile	BSW	300/AA/A	9" - 10.5"	10.7" on 9.5"	26.3"	790	10.0	1653@50	26.23 lbs
54687	265/35ZR19/XL (98Y)	30,000 Mile	BSW	300/AA/A	9" - 10.5"	10.7" on 9.5"	26.3"	790	9.0	1653@50	24.98 lbs
99954	265/35ZR19/XL (98Y)	30,000 Mile	BSW	300/AA/A	9" - 10.5"	10.7" on 9.5"	26.3"	790	9.0	1653@50	27.58 lbs
33791	265/35ZR19/XL (98Y)	30,000 Mile	BSW	300/AA/A	9" - 10.5"	10.7" on 9.5"	26.3"	790	10.0	1653@50	26.17 lbs
78123	265/35ZR20/XL (99Y)	30,000 Mile	BSW	300/AA/A	9" - 10.5"	10.7" on 9.5"	27.3"	761	9.0	1709@50	25.35 lbs

Pilot Super Sport - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
96755	265/35ZR21/XL (101Y)	30,000 Mile	BSW	300/AA/A	9" - 10.5"	10.7" on 9.5"	28.3"	735	10.0	1819@50	26.68 lbs
02725	265/35ZR21/XL (101Y)	30,000 Mile	BSW	300/AA/A	9" - 10.5"	10.7" on 9.5"	28.3"	735	10.0	1819@50	24.25 lbs
53518	265/35ZR22/XL (102Y)	30,000 Mile	BSW	300/AA/A	9" - 10.5"	10.7" on 9.5"	29.3"	709	10.0	1874@50	29.54 lbs
96083	265/40ZR18/XL 101Y	30,000 Mile	BSW	300/AA/A	9" - 10.5"	10.7" on 9.5"	26.3"	790	10.0	1819@50	27.09 lbs
13092	265/40ZR19/XL (102Y)	30,000 Mile	BSW	300/AA/A	9" - 10.5"	10.7" on 9.5"	27.4"	760	9.0	1874@51	24.98 lbs
12049	275/30ZR20/XL 97Y	30,000 Mile	BSW	300/AA/A	9" - 10"	10.9" on 9.5"	26.5"	784	9.0	1609@50	26.61 lbs
46347	275/30ZR21/XL (98Y)	30,000 Mile	BSW	300/AA/A	9" - 10"	10.9" on 9.5"	27.5"	756	9.5	1653@50	28.66 lbs
71226	275/35ZR18/XL (99Y)	30,000 Mile	BSW	300/AA/A	9" - 11"	10.9" on 9.5"	25.6"	814	8.5	1709@50	26.81 lbs
69959	275/35ZR19 (96Y)	30,000 Mile	BSW	300/AA/A	9" - 11"	10.9" on 9.5"	26.6"	783	10.0	1565@51	27.62 lbs
10300	275/35ZR19/XL (100Y)	30,000 Mile	BSW	300/AA/A	9" - 11"	10.9" on 9.5"	26.6"	783	10.0	1764@50	25.97 lbs
34965	275/35ZR20/XL (102Y)	30,000 Mile	BSW	300/AA/A	9" - 11"	10.9" on 9.5"	27.6"	755	9.0	1874@50	27.34 lbs
40782	275/35RF21 99Y	30,000 Mile	BSW	300/AA/A	9" - 11"	10.9" on 9.5"	28.5"	729	9.5	1709@51	34.61 lbs
16452	275/35ZR22/XL (104Y)	30,000 Mile	BSW	300/AA/A	9" - 11"	10.9" on 9.5"	29.6"	703	10.0	1984@50	29.76 lbs
02344	275/40ZR18 (99Y)	30,000 Mile	BSW	300/AA/A	9" - 11"	10.9" on 9.5"	26.7"	780	10.0	1709@51	26.65 lbs
84944	275/40ZR19/XL (105Y)	30,000 Mile	BSW	300/AA/A	9" - 11"	10.9" on 9.5"	27.7"	751	10.0	2039@50	29.32 lbs
05916	P285/30ZR19 (94Y)	30,000 Mile	BSW	300/AA/A	9.5" - 10.5"	11.4" on 10"	25.8"	807	7.4	1477@51	29.72 lbs
07078	285/30ZR19/XL (98Y)	30,000 Mile	BSW	300/AA/A	9.5" - 10.5"	11.4" on 10"	25.8"	807	9.5	1653@50	26.26 lbs
11313	P285/30ZR20 (95Y)	30,000 Mile	BSW	300/AA/A	9.5" - 10.5"	11.4" on 10"	26.8"	777	9.0	1521@51	32.08 lbs
71509	285/30ZR20/XL (99Y)	30,000 Mile	BSW	300/AA/A	9.5" - 10.5"	11.4" on 10"	26.8"	777	7.0	1709@50	24.54 lbs
80913	285/30ZR20/XL (99Y)	30,000 Mile	BSW	300/AA/A	9.5" - 10.5"	11.4" on 10"	26.8"	777	9.0	1709@50	26.72 lbs
92632	285/30ZR20/XL (99Y)	30,000 Mile	BSW	300/AA/A	9.5" - 10.5"	11.4" on 10"	26.8"	777	10.0	1709@50	26.76 lbs
48164	285/30ZR21/XL (100Y)	30,000 Mile	BSW	300/AA/A	9.5" - 10.5"	11.4" on 10"	27.8"	749	10.0	1764@50	28.44 lbs
22320	285/35ZR18/XL (101Y)	30,000 Mile	BSW	300/AA/A	9.5" - 11"	11.4" on 10"	25.9"	804	9.5	1819@50	28.11 lbs
10332	P285/35ZR19 (99Y)	30,000 Mile	BSW	300/AA/A	9.5" - 11"	11.4" on 10"	26.7"	774	10.0	1709@51	33.47 lbs

Pilot Super Sport - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
90864	285/35ZR20/XL (104Y)	30,000 Mile	BSW	300/AA/A	9.5" - 11"	11.4" on 10"	27.9"	746	9.0	1984@50	29.78 lbs
45895	285/35ZR21/XL 105Y	30,000 Mile	BSW	300/AA/A	9.5" - 11"	11.4" on 10"	28.9"	721	10.0	2039@50	29.59 lbs
87806	285/40ZR19 (103Y)	30,000 Mile	BSW	300/AA/A	9.5" - 11"	11.4" on 10"	28.0"	743	9.0	1929@51	29.89 lbs
78686	295/30ZR19/XL (100Y)	30,000 Mile	BSW	300/AA/A	10" - 11"	11.9" on 10.5"	26.0"	799	10.0	1764@50	28.17 lbs
01424	295/30ZR19/XL (100Y)	30,000 Mile	BSW	300/AA/A	10" - 11"	11.8" on 10.5"	26.0"	799	9.0	1764@50	31.06 lbs
02623	295/30ZR20/XL (101Y)	30,000 Mile	BSW	300/AA/A	10" - 11"	11.9" on 10.5"	27.0"	770	10.0	1819@50	29.19 lbs
10427	295/30ZR20/XL (101Y)	30,000 Mile	BSW	300/AA/A	10" - 11"	11.9" on 10.5"	27.0"	770	9.0	1819@50	29.61 lbs
25248	295/30ZR21/XL (102Y)	30,000 Mile	BSW	300/AA/A	10" - 11"	11.9" on 10.5"	28.0"	743	10.0	1874@50	30.03 lbs
85467	295/30ZR22/XL (103Y)	30,000 Mile	BSW	300/AA/A	10" - 11"	11.8" on 10.5"	29.0"	717	10.0	1929@50	28.66 lbs
07934	295/35ZR18/XL (103Y)	30,000 Mile	BSW	300/AA/A	10" - 11.5"	11.8" on 10.5"	26.1"	797	10.0	1929@50	29.43 lbs
08022	295/35ZR19 (100Y)	30,000 Mile	BSW	300/AA/A	10" - 11.5"	11.9" on 10.5"	27.1"	767	7.5	1764@51	28.97 lbs
10261	295/35ZR19/XL (104Y)	30,000 Mile	BSW	300/AA/A	10" - 11.5"	11.9" on 10.5"	27.1"	767	9.0	1984@51	28.13 lbs
37907	295/35ZR19/XL (104Y)	30,000 Mile	BSW	300/AA/A	10" - 11.5"	11.8" on 10.5"	27.1"	767	10.0	1984@50	28.51 lbs
28274	295/35ZR20 (101Y)	30,000 Mile	BSW	300/AA/A	10" - 11.5"	11.9" on 10.5"	28.1"	740	9.0	1819@51	30.84 lbs

Pilot Super Sport - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
09045	295/35ZR20/XL (105Y)	30,000 Mile	BSW	300/AA/A	10" - 11.5"	11.9" on 10.5"	28.1"	740	9.0	2039@50	30.86 lbs
70657	295/35ZR20/XL (105Y)	30,000 Mile	BSW	300/AA/A	10" - 11.5"	11.9" on 10.5"	28.1"	740	9.0	2039@50	30.29 lbs
48442	305/30ZR20/XL (103Y)	30,000 Mile	BSW	300/AA/A	10.5" - 11.5"	12.3" on 11"	27.2"	764	9.0	1929@50	30.91 lbs
44476	305/30ZR20/XL (103Y)	30,000 Mile	BSW	300/AA/A	10.5" - 12"	12.3" on 11"	27.2"	764	10.0	1929@50	31.33 lbs
08609	305/30ZR22/XL (105Y)	30,000 Mile	BSW	300/AA/A	10.5" - 11.5"	12.3" on 11"	29.3"	711	10.0	2039@50	33.07 lbs
39527	305/35ZR19 (102Y)	30,000 Mile	BSW	300/AA/A	10" - 12"	12.3" on 11"	27.4"	758	8.0	1874@51	30.69 lbs
84034	305/35ZR22/XL (110Y)	30,000 Mile	BSW	300/AA/A	10" - 12"	12.3" on 11"	30.4"	684	10.0	2337@50	28.66 lbs
41597	315/25ZR23/XL (102Y)	30,000 Mile	BSW	300/AA/A	11" - 12"	12.8" on 11.5"	29.2"	712	10.0	1874@50	34.11 lbs
19605	315/35ZR20/XL (110Y)	30,000 Mile	BSW	300/AA/A	10.5" - 12.5"	12.6" on 11"	28.7"	726	7.0	2337@50	33.27 lbs
79340	315/35ZR20/XL (110Y)	30,000 Mile	BSW	300/AA/A	10.5" - 12.5"	12.6" on 11"	28.7"	726	10.0	2337@50	34.5 lbs
74995	325/30ZR21/XL 108Y	30,000 Mile	BSW	300/AA/A	11" - 12"	13" on 11.5"	28.7"	725	10.0	2205@50	32.96 lbs
02430	P335/25ZR20 (99Y)	30,000 Mile	BSW	300/AA/A	11.5" - 12.5"	13.5" on 12"	26.6"	782	7.8	1709@51	33.93 lbs
07218	335/30ZR20/XL (108Y)	30,000 Mile	BSW	300/AA/A	11.5" - 12.5"	13.5" on 12"	28.0"	744	9.0	2205@50	34.94 lbs
29703	345/30ZR19/XL (109Y)	30,000 Mile	BSW	300/AA/A	11.5" - 12.5"	13.8" on 12"	27.2"	765	9.0	2271@50	34.83 lbs