

Premier A/S - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
65661	185/55R16 83H	60,000 Mile	BSW	640/A/A	5" - 6.5"	7.64" on 6"	24.02"	866	8.5	1074@44	17.66 lbs
99018	185/65R15 88H	60,000 Mile	BSW	640/A/A	5" - 6.5"	7.44" on 5.5"	24.45"	851	8.5	1235@44	17.95 lbs
16874	195/55R15 85V	60,000 Mile	BSW	640/A/A	5.5" - 7"	7.91" on 6"	23.43"	888	8.5	1135@44	17.53 lbs
14687	195/55R16 87V	60,000 Mile	BSW	640/A/A	5.5" - 7"	7.91" on 6"	24.41"	852	8.5	1201@44	18.83 lbs
47950	195/60R15 88H	60,000 Mile	BSW	640/A/A	5.5" - 7"	7.91" on 6"	24.21"	859	8.5	1235@44	17.81 lbs
64848	195/60R16 89H	60,000 Mile	BSW	640/A/A	5.5" - 7"	7.91" on 6"	25.2"	825	8.5	1279@44	19.62 lbs
55457	195/65R15 91H	60,000 Mile	BSW	640/A/A	5.5" - 7"	7.91" on 6"	25.0"	832	8.5	1356@44	18.87 lbs
28207	205/50R17/XL 93H	60,000 Mile	BSW	640/A/A	5.5" - 7.5"	8.43" on 6.5"	25.12"	828	8.5	1433@50	21.74 lbs
93054	205/50R17/XL 93V	60,000 Mile	BSW	640/A/A	5.5" - 7.5"	8.43" on 6.5"	25.12"	828	8.5	1433@50	21.74 lbs
03364	205/55R16 91H	60,000 Mile	BSW	640/A/A	5.5" - 7.5"	8.43" on 6.5"	24.88"	836	8.5	1356@44	20.02 lbs
28886	205/55R16 91V	60,000 Mile	BSW	640/A/A	5.5" - 7.5"	8.43" on 6.5"	24.88"	836	8.5	1356@44	20.13 lbs
43030	205/60R16 92H	60,000 Mile	BSW	640/A/A	5.5" - 7.5"	8.23" on 6"	25.67"	810	8.5	1389@44	20.24 lbs
05577	205/60R16 92V	60,000 Mile	BSW	640/A/A	5.5" - 7.5"	8.23" on 6"	25.67"	810	8.5	1389@44	20.44 lbs
06189	205/65R15 94H	60,000 Mile	BSW	640/A/A	5.5" - 7.5"	8.23" on 6"	25.47"	817	8.5	1477@44	20.37 lbs
13768	205/65R16 95H	60,000 Mile	BSW	640/A/A	5.5" - 7.5"	8.23" on 6"	26.46"	786	8.5	1521@51	21.52 lbs
30054	215/45R17 87H	60,000 Mile	BSW	640/A/A	7" - 8"	8.39" on 7"	24.65"	844	8.5	1201@44	20.61 lbs
28504	215/45R17 87V	60,000 Mile	BSW	640/A/A	7" - 8"	8.39" on 7"	24.65"	844	8.5	1201@44	20.61 lbs
65481	215/50R17 91H	60,000 Mile	BSW	640/A/A	6" - 7.5"	8.9" on 7"	25.51"	815	8.5	1356@44	22.71 lbs
90458	215/50R17/XL 95V	60,000 Mile	BSW	640/A/A	6" - 7.5"	8.9" on 7"	25.51"	815	8.5	1521@50	22.71 lbs
09762	215/55R16 93H	60,000 Mile	BSW	640/A/A	6" - 7.5"	8.9" on 7"	25.28"	823	8.5	1433@44	20.97 lbs
33915	215/55R17 94H	60,000 Mile	BSW	640/A/A	6" - 7.5"	8.9" on 7"	26.3"	791	8.5	1477@44	22.71 lbs
73446	215/55R17 94V	60,000 Mile	BSW	640/A/A	6" - 7.5"	8.9" on 7"	26.3"	791	8.5	1477@44	22.77 lbs
37604	215/55R18 95H	60,000 Mile	BSW	640/A/A	6" - 7.5"	8.9" on 7"	27.28"	762	8.5	1521@44	23.24 lbs
11712	215/60R16 95H	60,000 Mile	BSW	640/A/A	6" - 7.5"	8.7" on 6.5"	26.14"	796	8.5	1521@44	21.25 lbs

Premier A/S - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
22475	215/60R16 95V	60,000 Mile	BSW	640/A/A	6" - 7.5"	8.7" on 6.5"	26.14"	796	8.5	1521@44	21.43 lbs
06237	215/60R17 96H	60,000 Mile	BSW	640/A/A	6" - 7.5"	8.7" on 6.5"	27.17"	766	8.5	1565@44	23.77 lbs
37417	225/45R17 91H	60,000 Mile	BSW	640/A/A	7" - 8.5"	8.86" on 7.5"	24.96"	833	8.5	1356@44	22.62 lbs
88269	225/45R17 91V	60,000 Mile	BSW	640/A/A	7" - 8.5"	8.86" on 7.5"	24.96"	833	8.5	1356@44	22.6 lbs
29852	225/45R18 91V	60,000 Mile	BSW	640/A/A	7" - 8.5"	8.86" on 7.5"	25.94"	802	8.5	1356@44	23.55 lbs
22075	225/50R17 94H	60,000 Mile	RRBL	640/A/A	6" - 8"	9.17" on 7"	25.91"	803	8.5	1477@44	22.0 lbs
79471	225/50R17 94V	60,000 Mile	BSW	640/A/A	6" - 8"	9.17" on 7"	25.91"	803	8.5	1477@44	22.35 lbs
04853	225/50R18 95H	60,000 Mile	BSW	640/A/A	6" - 8"	9.17" on 7"	26.89"	774	8.5	1521@44	24.23 lbs
87266	225/55R16 95H	60,000 Mile	BSW	640/A/A	6" - 8"	9.17" on 7"	25.75"	808	8.5	1521@44	21.87 lbs
05661	225/55R16 95V	60,000 Mile	BSW	640/A/A	6" - 8"	9.17" on 7"	25.75"	808	8.5	1521@44	21.87 lbs
48163	225/55R17 97H	60,000 Mile	BSW	640/A/A	6" - 8"	9.17" on 7"	26.77"	777	8.5	1609@44	23.41 lbs
28800	225/55R17 97V	60,000 Mile	BSW	640/A/A	6" - 8"	9.17" on 7"	26.77"	777	8.5	1609@44	24.07 lbs
97967	225/55R18 98H	60,000 Mile	BSW	640/A/A	6" - 8"	9.17" on 7"	27.76"	749	8.5	1653@44	24.38 lbs
67121	225/60R16 98H	60,000 Mile	BSW	640/A/A	6" - 8"	8.98" on 6.5"	26.61"	782	8.5	1653@44	24.4 lbs
67961	225/60R17 99H	60,000 Mile	BSW	640/A/A	6" - 8"	8.98" on 6.5"	27.64"	753	8.5	1709@44	25.11 lbs
08300	225/60R18 100H	60,000 Mile	BSW	640/A/A	6" - 8"	8.98" on 6.5"	28.62"	727	8.5	1764@44	25.86 lbs
47563	225/65R16 100H	60,000 Mile	BSW	640/A/A	6" - 8"	8.98" on 6.5"	27.48"	757	8.5	1764@44	24.8 lbs
92084	235/45R17 94H	60,000 Mile	BSW	640/A/A	7.5" - 9"	9.29" on 8"	25.35"	821	8.5	1477@44	23.77 lbs
96630	235/45R18 94H	60,000 Mile	BSW	640/A/A	7.5" - 9"	9.29" on 8"	26.34"	790	8.5	1477@44	24.89 lbs
02608	235/45R18 94V	60,000 Mile	BSW	640/A/A	7.5" - 9"	9.29" on 8"	26.34"	790	8.5	1477@44	24.89 lbs
20973	235/50R17 96H	60,000 Mile	BSW	640/A/A	6.5" - 8.5"	9.65" on 7.5"	26.3"	791	8.5	1565@44	23.35 lbs
95088	235/55R17 99H	60,000 Mile	BSW	640/A/A	6.5" - 8.5"	9.65" on 7.5"	27.17"	766	8.5	1709@44	25.31 lbs
04213	235/55R18 100V	60,000 Mile	BSW	640/A/A	6.5" - 8.5"	9.65" on 7.5"	28.15"	739	8.5	1764@44	26.74 lbs
10396	235/60R16 100H	60,000 Mile	BSW	640/A/A	6.5" - 8.5"	9.45" on 7"	27.09"	768	8.5	1764@44	25.95 lbs

Premier A/S - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
34004	235/60R18 103H	60,000 Mile	BSW	640/A/A	6.5" - 8.5"	9.45" on 7"	29.09"	715	8.5	1929@44	27.78 lbs
19530	235/65R16 103H	60,000 Mile	BSW	640/A/A	6.5" - 8.5"	9.45" on 7"	28.03"	742	8.5	1929@44	27.05 lbs
36126	245/45R17 95H	60,000 Mile	BSW	640/A/A	7.5" - 9"	9.57" on 8"	25.67"	810	8.5	1521@44	24.54 lbs
08729	245/45R18/XL 100V	60,000 Mile	BSW	640/A/A	7.5" - 9"	9.57" on 8"	26.65"	780	8.5	1764@50	26.1 lbs
38379	245/45R19 98V	60,000 Mile	BSW	640/A/A	7.5" - 9"	9.57" on 8"	27.68"	751	8.5	1653@44	27.14 lbs
11373	245/50R17 99V	60,000 Mile	BSW	640/A/A	7" - 8.5"	9.96" on 7.5"	26.69"	779	8.5	1709@44	25.44 lbs