

Primacy HP - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
86391	205/50R17 89W	30,000 Mile	BSW	240/A/A	5.5" - 7.5"	8.4" on 6.5"	25.1"	828	10.0	1279@51	25.68 lbs
05435	205/55R16 91V	45,000 Mile	BSW	240/A/A	5.5" - 7.5"	8.4" on 6.5"	24.9"	836	10.0	1356@51	19.95 lbs
07661	205/60R16 92W	35,000 Mile	BSW	240/A/A	5.5" - 7.5"	8.2" on 6"	25.7"	810	10.0	1389@51	20.99 lbs
30333	215/45R17 87W	35,000 Mile	BSW	240/A/A	7" - 8"	8.4" on 7"	24.7"	844	9.5	1201@51	20.79 lbs
33484	215/55R16 93H	45,000 Mile	BSW	240/A/A	6" - 7.5"	8.9" on 7"	25.3"	823	10.0	1433@51	22.27 lbs
04743	225/45R17 91W	35,000 Mile	BSW	240/A/A	7" - 8.5"	8.9" on 7.5"	25.0"	833	10.0	1356@51	20.83 lbs
73723	225/45R17 91W	35,000 Mile	BSW	240/A/A	7" - 8.5"	8.9" on 7.5"	25.0"	833	10.0	1356@51	21.32 lbs
25049	225/50R16 92W	35,000 Mile	BSW	240/A/A	6" - 8"	9.2" on 7"	24.9"	836	10.0	1389@51	22.53 lbs
73416	235/45R17 94W	35,000 Mile	BSW	240/A/A	7.5" - 9"	9.3" on 8"	25.4"	821	10.0	1477@51	22.71 lbs
83888	235/55R17 99W	35,000 Mile	BSW	240/A/A	6.5" - 8.5"	9.7" on 7.5"	27.2"	766	10.0	1709@51	26.23 lbs
27111	245/40R17 91W	35,000 Mile	BSW	240/A/A	8" - 9.5"	9.8" on 8.5"	24.7"	841	10.0	1356@51	22.69 lbs
62364	245/40R19 94Y	30,000 Mile	BSW	240/A/A	8" - 9.5"	9.8" on 8.5"	26.7"	778	10.0	1477@51	29.76 lbs
05816	255/45R18 99Y	35,000 Mile	BSW	240/A/A	8" - 9.5"	10" on 8.5"	27.1"	769	10.0	1709@51	27.01 lbs
15994	275/35R19 96Y	30,000 Mile	BSW	240/A/A	9" - 11"	10.9" on 9.5"	26.6"	783	10.0	1565@51	32.03 lbs