

Primacy MXV4 - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
01991	P205/55R16 89H	60,000 Mile	BSW	620/A/A	5.5" - 7.5"	8.4" on 6.5"	24.9"	836	9.5	1279@51	20.7 lbs
08357	P215/55R17 93V	60,000 Mile	BSW	500/A/A	6" - 7.5"	8.9" on 7"	26.3"	791	9.5	1433@51	22.73 lbs
28637	215/55R17 94V	60,000 Mile	BSW	500/A/A	6" - 7.5"	8.9" on 7"	26.3"	791	9.5	1477@44	23.63 lbs
02647	225/55R17 97V	60,000 Mile	BSW	620/A/A	6" - 8"	9.2" on 7"	26.8"	777	11.0	1609@44	26.57 lbs
22559	P235/50R19 99V	60,000 Mile	BSW	500/A/A	6.5" - 8.5"	9.7" on 7.5"	28.3"	735	9.5	1709@44	27.4 lbs
38169	P235/60R17 100T	60,000 Mile	BSW	500/A/A	6.5" - 8.5"	9.5" on 7"	28.1"	740	9.5	1764@44	26.37 lbs
35096	P235/60R18 102T	60,000 Mile	BSW	500/A/A	6.5" - 8.5"	9.45" on 7"	29.09"	715	10.0	1874@44	29.41 lbs
66126	P235/65R17 103T	60,000 Mile	BSW	500/A/A	6.5" - 8.5"	9.5" on 7"	29.1"	716	10.0	1929@44	29.41 lbs